

GREEN ROOF  
TECHNICAL DATA

## XF 300 SEDUM MAT

### DESCRIPTION

The XF 300 Sedum Mat is an easy to handle pre-vegetated mat containing a variety of sedum species. Pre-cultivated mats are flexible, compressible, and easy to cut for a seamless installation.

### PHYSICAL PROPERTIES

Vegetation	Mix of sedum species depending on location and availability.
Pre-cultivated Mat Dimension	6.56 ft L x 3.28 ft W (2 m x 1 m) Area: 21.5 f ft <sup>2</sup> (2 m <sup>2</sup> )
Thickness	0.67 inch (17 mm)
Weight	Dry: 2.8 lb/ft <sup>2</sup> (13.6 kg/m <sup>2</sup> ) Field: 3.5 - 4.1 lb/ft <sup>2</sup> (17 - 20 kg/m <sup>2</sup> )

### ADVANTAGES

- Fire Resistant - Class A fire rated product for roofing.
- Excellent for flexibility & compressibility.
- Non-biodegradable fibers.
- Non-woven root penetrating backing.
- Fast installation reducing labor cost.

### APPLICATION

Use XF 300 Sedum Mat in the green roof system, as the vegetation component.

### SHIPPING

Roll: 3.3 ft L x 1 - 1.2 ft dia. (1 m x 30.5 - 36.5 cm)  
Roll Weight: 75 - 88 lb (34 - 40 kg)  
Pallet Maximum: 258.24 ft<sup>2</sup> (24 m<sup>2</sup>)  
Dry Van 48-ft FTL: 6200 ft<sup>2</sup> (576 m<sup>2</sup>)